

AUXILIARY CONTROLS | PEGASUS SERIES
AUXILIARY CONTROLS | PEGASUS SERIES
EMERGENCY PUSH BUTTONS Ø22 | EN ISO 13850

	TYPE	COLOUR INDEX	CODE	WEIGHT (gr)	MIN. PACK QUANTITY	SIZES
MUSHROOM OPERATOR Ø30 TWIST TO RELEASE			PPFN1R3N	42	10	
	TYPE	COLOUR INDEX	CODE	WEIGHT (gr)	MIN. PACK QUANTITY	SIZES
MUSHROOM OPERATOR WITH VISION Ø30 TWIST TO RELEASE			PPFN1R3S	44	10	
	TYPE	COLOUR INDEX	CODE	WEIGHT (gr)	MIN. PACK QUANTITY	SIZES
MUSHROOM OPERATOR Ø40 TWIST TO RELEASE			PPFN1R4N	44	10	
	TYPE	COLOUR INDEX	CODE	WEIGHT (gr)	MIN. PACK QUANTITY	SIZES
MUSHROOM OPERATOR WITH VISION Ø40 TWIST TO RELEASE			PPFN1R4S	46	10	
	TYPE	COLOUR INDEX	CODE	WEIGHT (gr)	MIN. PACK QUANTITY	SIZES
MUSHROOM OPERATOR Ø60 TWIST TO RELEASE			PPFN1R6N	50	10	
	TYPE	COLOUR INDEX	CODE	WEIGHT (gr)	MIN. PACK QUANTITY	SIZES
MUSHROOM OPERATOR WITH VISION Ø60 TWIST TO RELEASE			PPFN1R6S	52	10	

EMERGENCY PUSH BUTTONS Ø22 | EN ISO 13850

	TYPE	COLOUR INDEX	CODE	WEIGHT (gr)	MIN. PACK QUANTITY	SIZES
MUSHROOM OPERATOR Ø40 WITH KEY RELEASE			PPFN1C4NX (non EN ISO 13850)	76	10	
	TYPE	COLOUR INDEX	CODE	WEIGHT (gr)	MIN. PACK QUANTITY	SIZES
MUSHROOM OPERATOR WITH VISION Ø40 PUSH-PULL			PPFN1P4N	44	10	
	TYPE	COLOUR INDEX	CODE	WEIGHT (gr)	MIN. PACK QUANTITY	SIZES
MUSHROOM OPERATOR Ø40 PUSH-PULL WITH VISION			PPFN1P4S	46	10	
	TYPE	COLOUR INDEX	CODE	WEIGHT (gr)	MIN. PACK QUANTITY	SIZES
MUSHROOM OPERATOR Ø40 PUSH-PULL WITH COLOUR CAP			PPFN1P4C	45	10	
	TYPE	COLOUR INDEX	CODE	WEIGHT (gr)	MIN. PACK QUANTITY	SIZES
MUSHROOM OPERATOR Ø40 PUSH-PULL WITH LENS CAP			PPFL1P4N	45	10	

TECHNICAL NOTES

- All operators comply with the relevant European standard.
- EN ISO 13850: Machine safety - Emergency stop operators, functional characteristics - Design guidelines.
- IEC/EN6097-5-1.
- Comply with the standard IEC/EN60204-1: Machine safety - Machine electrical circuits - General guidelines.
- The push buttons are designed with a load charge mechanism to ensure a reliable operation and stoppage, or blockage, in the activate position. The combination with positive switching NC contacts and the presence of the "status" indicator on some models, guarantee a high degree of reliability and effectiveness.